



## Plaster and Render Beads

These beads are designed to give true corners and edges to plaster and render where thick or 'rough' coats are required. Fixing is easy using plaster dabs or galvanised nails (with galvanised beads) and the mesh wings provide resistance to cracking while offering a good key to the plaster or render.



### Product

## GEB Galvanised Plasterboard Edge Bead

A bead to reinforce the edges of plasterboard which can be fixed on either with the perforated flange on the face of the board by nailing and skimmed over with the short flange on the board face for a decorative finish.

Generally for internal use only.

Available in galvanised steel grade DX.51. Z275g to BS EN 10346:200.  
Manufactured to BS EN 13658-1: 2005

Sizes	Per Box:
2.4m	50 lengths
2.7m	50 lengths
3.0m	50 lengths

### Storage & Information

To prevent distortion and damage the GAB bead should be kept dry and stored above the ground on a flat surface.

Any potential corrosion in galvanised beads will only become apparent during the initial drying out period of the plaster or during periods of dampness and heavy condensation. The drying out period (which should be a maximum of 5-7 days) should be kept to a minimum.

#### Safety Precautions

GAB Galvanised Angle Bead is manufactured from sheared plate and strip so may contain sharp edges. Suitable personal protection should always be used when handling/installing these products.